

TUERCA REMACHABLE CABEZA ANCHA

Métrica	L Longitud [mm]	D ø cabeza [mm]	d ø caña [mm]	S Espesor cabeza [mm]	Espesor a fijar [mm]	ø taladro previo [mm]
M3	10	7	4.9	1.0	0.5 ÷ 3.0	5
M4	10	9	5.9	1.1	0.3 ÷ 3.0	6
	11.5				3.1 ÷ 4.0	
M5	12	10	6.9	1.1	0.3 ÷ 3.0	7
	15				3.1 ÷ 4.0	
M6	14.5	12	8.9	1.6	0.5 ÷ 3.0	9
	16				3.1 ÷ 4.1	
M8	16	15	10.9	1.6	0.5 ÷ 3.0	11
	18.5				3.1 ÷ 5.5	
M10	17	19	12.9	2.1	0.5 ÷ 3.0	13
	22				3.1 ÷ 6.0	
M12	23	23	15.9	2.1	1.0 ÷ 4.0	16

**CARACTERÍSTICAS MECÁNICAS
CARGA RECOMENDADA**

Métrica [-]	Tracción [KN]	Cortadura [KN]	Par [Nm]
M3	4.9	0.98	3.0
M4	4.9	1.66	4.5
M5	11.088	2.74	5.4
M6	17.65	3.43	11
M8	27.45	4.41	29
M10	28.43	4.9	32
M12	48.05	6.86	44.2

